

# Cobra Snake Fibreglass Duct Rod Accessories »



## Replacement Vertical Dispenser

Cat. No.	Description	Suits Rod Dia (mm)	Suits Rod Length (m)	Weight (kg)	Pack Qty
SCLVSD	Small vertical dispenser	4.5	20 - 80	3.2	1
SCLVMD	Medium vertical dispenser	6.0, 7.5	40 - 150	8.6	1
SCLVLD	Large vertical dispenser	11.0	100 - 300	17.4	1

## Repair Kits

Designed for repairing damaged fibreglass duct rods.



Cat. No.	Description	Suits Rod Dia (mm)	Glue	Kit Accessories	Pack Qty
SCLR45	Repair kit for 4.5mm fibreglass rod	4.5	Special adhesive 3g	M5 starting ends x2, coupling joint x1	1
SCLR60	Repair kit for 6mm fibreglass rod	6	2 - component epoxy Resin 24ml	M6 starting ends x2, coupling joint x1	1
SCLR75	Repair kit for 7.5mm fibreglass rod	7.5	2 - component epoxy Resin 24ml	M12 starting ends x2, coupling joint x1	1
SCLR110	Repair kit for 11mm fibreglass rod	11	2 - component epoxy Resin 24ml	M12 starting ends x2, coupling joint x1	1

## Rod Starting Ends


The rod starting end is a threaded brass connector used for connecting accessories to fibreglass rods.



Cat. No.	Description	Suits Rod Dia (mm)	Thread Size	Weight (g)	Pack Qty
SCLSE45	Rod Starting End	4.5	M5	6	1
SCLSE60	Rod Starting End	6.0	M6	12	1
SCLSE75	Rod Starting End	7.5	M12	43	1
SCLSE110	Rod Starting End	11.0	M12	68	1

## Coupling Joints

The coupling joint is used to repair/refurbish damaged fibreglass rods.



Cat. No.	Description	Suits Rod Dia (mm)	Weight (g)	Pack Qty
SCLCJ45	Coupling Joint	4.5	8	1
SCLCJ60	Coupling Joint	6.0	8	1
SCLCJ75	Coupling Joint	7.5	65	1
SCLCJ110	Coupling Joint	11.0	86	1

## Roller Guides

Guides the fibreglass rod around bends with ease, and helps stop fibreglass rod from getting jammed under existing cable already in conduit.



Cat. No.	Description	Suits Rod Dia (mm)	Thread Size	Roller Dia (mm)	Weight (g)	Pack Qty
SCLRG45	Roller Guide	4.5	M5	25	24	1
SCLRG60	Roller Guide	6.0	M6	25	24	1
SCLRG75110	Roller Guide	7.5, 11.0	M12	50	193	1

## Flexible Guides

The flexible guide is a fine spring loaded brass head, to help the fibreglass rod negotiate bends while traversing pipes & conduits.



Cat. No.	Description	Suits Rod Dia (mm)	Thread Size	Weight (g)	Pack Qty
SCLFG3045	Flexible guide for fibreglass rods	4.5	M5	8	1
SCLFG60	Flexible guide for fibreglass rods	6.0	M6	8	1

## Starting Spinner with Shackle

The shackle fitting is used to provide a larger pulling loop for attaching pull line or rope.



Cat. No.	Description	Suits Rod Dia (mm)	Thread Size	Weight (g)	Pack Qty
SCLSS45	Starting spinner with shackle	4.5	M5	24	1
SCLSS60	Starting spinner with shackle	6.0	M6	24	1
SCLSS75110	Starting spinner with shackle	7.5, 11.0	M12	147	1

## Pulling Eyelets

Attached to the fibreglass rod end, pulling eyelets are used to pull wire & drawline into conduits and are fully removable.



Cat. No.	Description	Suits Rod Dia (mm)	Thread Size	Weight (g)	Pack Qty
SCLPE45	Pulling eyelet for fibreglass rod	4.5	M5	8	1
SCLPE60	Pulling eyelet for fibreglass rod	6.0	M6	8	1

## Rubber Pulling Disc

Pulling Grips are a special all purpose rubber pulling hand disc, designed to firmly grip circular objects such as cable, fish rods & fish tapes.



Cat. No.	Description	Diameter Range (mm)	Weight (g)	Pack Qty
SPRD36	Rubber Pulling Disc	3 - 6	40	1
SPRD612	Rubber Pulling Disc	6 - 12	40	1